



Multi Wall Polycarbonate

Product	Shading	Light	U	Weight Kg's	Number of Walls
	Coefficient	Transmission	Value W/m ² K		
4mm Clear	0.75	82%	3.8	0.8	Twin Box
6mm Clear	0.75	80%	3.5	1.2	Twin Box
10mm Clear	0.75	79%	3	1.5	Twin Box
10mm Bronze	0.45	35%	3	1.5	Twin Box
10mm Opal	0.52	30%	3	1.5	Twin Box
16mm Clear	0.75	76%	2.3	2.5	Three Box
16mm Bronze	0.45	35%	2.3	2.5	Three Box
16mm Opal	0.52	25%	2.3	2.5	Three Box
25mm Clear	0.75	62%	1.4	3.1	Seven X
25mm Bronze	0.45	11%	1.4	3.1	Seven X
25mm Opal	0.52	28%	1.4	3.1	Five X
25mm Bronze/Opal	0.42	8%	1.4	3.1	Seven X
25mm Heatguard/Opal	0.30	7%	1.4	3.1	Seven X
32mm Clear	0.75	63%	1.3	3.6	Seven Box
32mm Bronze	0.45	7%	1.3	3.6	Seven Box
32mm Opal	0.52	33%	1.3	3.6	Seven Box
32mm Bronze/Opal	0.42	8%	1.3	3.6	Seven Box
32mm Heatguard/Opal	0.30	7%	1.3	3.6	Seven Box
35mm Clear	0.75	63%	1.2	3.8	Seven Box
35mm Bronze	0.45	7%	1.2	3.8	Seven Box
35mm Opal	0.52	33%	1.2	3.8	Seven Box
35mm Bronze/Opal	0.42	8%	1.2	3.8	Seven Box
35mm Heatguard/Opal	0.30	7%	1.2	3.8	Seven Box

All Material Class 1 Fire Rating BS476/7

Product Colour Tints Subject To Manufacturers Production Tolerances

Information Correct As of January 2020

Sales Office 01529 461867 Option 2

sales@molan-uk.com